

Portable fire extinguisher filled with 3 Kg. of ABC powder with permanent pressure of nitrogen. It is suitable for class A,B,C fires.

SPECIFICATIONS

fire rating	13A 89B
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	3kg powder ABC
propellant agent	40g nitrogen
minimum pressure (-20°C)	12,5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar

DIMENSIONS

extinguisher height	480 mm
cylinder diameter	110 mm
wall thickness	1,5 mm
cylinder volume	3,45 l
total weight	5 kg

CERTIFICATES

Producto homologado y certificado acorde con la directiva 2014/68/UE y la normativa UNE-EN3-7 y EN3-10.



Aluminium valve



Steely neck ring



Membrane pressure gauge



Fire rating:

Class A, B C, electrical fires up to 50.000V.



Benefits:

It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



Do not use for: class F, D fires.

nº	piece	description
1	3P cylinder	DC04 EN 10130 steel. Polyester paint. Steel bar roll M30x1,5
2	3P dip tube	polyethylene
3	valve o-ring	red-coloured Hytrel
4	3P nozzle	ABS
5	ES powder valve	aluminium
6	safety pin	with 3,5x34mm stainless steel hole
7	ELITEX safety seal	red-coloured polypropylene
8	pressure gauge	gear type. Nickel plated housing 23 mm M10x1
9	vehicle bracket 2P/3P	polypropylene
10	3P ELITE extinguisher label	vinyl
11	extinguisher agent	ABC dry powder

** Spare o-rings and seals are supplied in green colour.*