

Portable fire extinguisher with trolley filled with 25 l. of water + AFFF additive. It is suitable for class A, B fires

SPECIFICATIONS

fire rating	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	25L water + AFFF
propellant agent	225g nitrogen
minimum pressure (-20°C)	16 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar

DIMENSIONS

extinguisher height	1000 mm
cylinder diameter	250mm
wall thickness	2,5 / 3 mm
cylinder volume	29 l
total weight	40,5 kg

CERTIFICATES

Approved certified product under 2014/68/UE directive.



Thermoplastic cover



Section extinguisher



Shower effect nozzle



Fire rating:
Class A, B and electrical fires of up to 35.000V. Warehouses, parking areas, shopping malls...



Benefits:
Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing.



Do not use for: class F, C, D fires.

No cleaning or recycling expenses.

n°	piece	description
1	25FOAM cylinder	DC04 EN 10130 steel. Polyester paint with M30x1,5 steel bar. Thermoplastic lining.
2	25FOAM hose	Polyamide 6 nozzle. PVC hose with nylon mesh reinforcement.
3	25 FOAM dip tube	polyethylene
4	EL FOAM valve	brass
5	safety pin	with 3,5x34mm stainless steel hole
6	ELITEX safety seal	red-coloured polypropylene
7	safety seal	membrane type. 23 mm M10x1 nickel casing
8	valve o-ring	red-coloured Hytrel
9	wheel	rubber and polypropylene
10	washer	polypropylene
11	25FOAM extinguisher label	vynil
12	extinguisher agent	water + AFFF additive

* Spare o-rings and seals are supplied in green colour.