



**el it e x**<sup>®</sup>

*providig your safety*

*p r o d u c t   b r o c h u r e   2 0 2 2*


*Portable fire extinguisher filled with 1 Kg.  
of ABC powder with permanent pressure of nitrogen.  
It is suitable for class A,B,C fires.*

**SPECIFICATIONS**

fire rating	5A 21B
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	1kg powder ABC
propellant agent	20g nitrogen
minimum pressure (-20°C)	12,5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



Steely neck ring



membrane pressure gauge



**Fire rating:**  
Class A, B C, electrical fires up to 50.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

*Product approved under directive and regulation in force.*

ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.


*Portable fire extinguisher filled with 2 Kg. of ABC powder with permanent pressure of nitrogen. It is suitable for class A,B,C fires.*

**SPECIFICATIONS**

fire rating	8A 34B
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	2kg powder ABC
propellant agent	20g nitrogen
minimum pressure (-20°C)	12, 5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



Steely neck ring



membrane pressure gauge



**Fire rating:**  
Class A, B C, electrical fires up to 50.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

*Product approved under directive and regulation in force.*



ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.



**SERIES: POWDER  
MODEL: 3P ELITE**

*Portable fire extinguisher filled with 3 Kg. of ABC powder with permanent pressure of nitrogen. It is suitable for class A,B,C fires.*

**SPECIFICATIONS**

fire rating	13A 89B
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	3kg powder ABC
propellant agent	40g nitrogen
minimum pressure (-20°C)	12, 5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



Steely neck ring



membrane pressure gauge



**Fire rating:**  
Class A, B C, electrical fires up to 50.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

*Product approved under directive and regulation in force.*

*Portable fire extinguisher filled with 6 Kg. of ABC powder with permanent pressure of nitrogen. It is suitable for class A,B,C fires.*



ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.

**SPECIFICATIONS**

fire rating	27A 183B
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	6kg powder ABC
propellant agent	80g nitrogen
minimum pressure (-20°C)	12, 5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



Steely neck ring



membrane pressure gauge



Maintenance tag from distributor.



Venturi effect difusser



**Fire rating:**  
Class A, B C, electrical fires up to 50.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

*Product approved under directive and regulation in force.*

*Portable fire extinguisher filled with 6 Kg. of ABC powder with permanent pressure of nitrogen. It is suitable for class A,B,C fires.*




ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.

**SPECIFICATIONS**

fire rating	34A 233B
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	6kg powder ABC
propellant agent	80g nitrogen
minimum pressure (-20°C)	12, 5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



Steely neck ring



membrane pressure gauge



Maintenance tag from distributor.



Venturi effect difusser



**Fire rating:**  
Class A, B C, electrical fires up to 50.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

*Product approved under directive and regulation in force.*



**SERIES: POWDER**  
**MODEL: 6P AUTOMATIC**  
**ELITE PLUS**

Portable fire extinguisher filled with 6 Kg. ABC Powder and permanent pressure of nitrogen.  
 It is suitable for Class A, B, C fires

**SPECIFICATIONS**

fire rating	-
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	6kg powder ABC
propellant agent	80g nitrogen
minimum pressure (-20°C)	12,5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



membrane pressure gauge



**Fire rating:** all diesel-powered boilers, inflammable deposits, class A, B C and electrical fires up to 50.000V.



**Benefits:** quick extinguishing as it offers 24h protection and it does not require human presence. When temperatures get higher than 68°C the extinguisher starts working automatically. It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. Sturdy and stable in extreme temperatures.



**Do not use for:** gas powered boilers or class F and D fires.

Product approved under directive and regulation in force.

ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.

Portable fire extinguisher filled with 9 Kg. of ABC powder with permanent pressure of nitrogen. It is suitable for class A,B,C fires.



ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.

**SPECIFICATIONS**

fire rating	43A 233B
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	9kg powder ABC
propellant agent	140g nitrogen
minimum pressure (-20°C)	12, 5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



Steely neck ring



membrane pressure gauge



Maintenance tag from distributor.



Venturi effect difusser



**Fire rating:**  
Class A, B, C, electrical fires up to 50.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

Product approved under directive and regulation in force.

Portable fire extinguisher filled with 9 Kg. ABC Powder and permanent pressure of nitrogen.  
 It is suitable for Class A, B, C fires

**SPECIFICATIONS**

fire rating	-
temperature range	-20°C/+60°C
electrical fires	up to 50.000 V
extinguisher agent	9kg powder ABC
propellant agent	140g nitrogen
minimum pressure (-20°C)	12,5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Aluminium valve.



membrane pressure gauge



**Fire rating:** all diesel-powered boilers, inflammable deposits, class A, B C and electrical fires up to 50.000V.



**Benefits:** quick extinguishing as it offers 24h protection and it does not require human presence. When temperatures get higher than 68°C the extinguisher starts working automatically. It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. Sturdy and stable in extreme temperatures.



**Do not use for:** gas powered boilers or class F and D fires.

Product approved under directive and regulation in force.

ELITEX, as manufacturer of fire extinguishers guarantees all its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.

*Portable fire extinguisher filled with 25 Kg.  
ABC Powder and permanent pressure of nitrogen.  
It is suitable for Class A,B,C fires*

#### SPECIFICATIONS

fire rating	A IVB C
temperature range	-20°C/+60°C
electrical fires	up to 1.000 V
extinguisher agent	25kg powder ABC
propellant agent	300g nitrogen
minimum pressure (-20°C)	12,5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



*Enhanced hose which supports greater precision and flow.*



*membrane pressure gauge*



**Fire rating:**  
Class A, B C, electrical fires up to 1.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

*Product approved under directive and regulation in force.*

Portable fire extinguisher filled with 50 Kg.  
ABC Powder and permanent pressure of nitrogen  
It is suitable for Class A,B,C fires

#### SPECIFICATIONS

fire rating	A IVB C
temperature range	-20°C/+60°C
electrical fires	up to 1.000 V
extinguisher agent	50kg powder ABC
propellant agent	500g nitrogen
minimum pressure (-20°C)	12,5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Enhanced hose which supports greater precision and flow.



membrane pressure gauge



**Fire rating:**  
Class A, B C, electrical fires up to 1.000V.



**Benefits:**  
It is suitable for almost any kind of fires. Non-toxic. It does not conduct electricity. It is sturdy and stable in extreme temperatures.



**Do not use for:** class F, D fires.

Product approved under directive and regulation in force.



**SERIES: FOAM**  
**MODEL: 2 FOAM "F" ELITE**  
**(special kitchen and home)**

*Portable fire extinguisher filled with 2 l. of water + AFFF additive.  
 It is intended for fires caused by use of oils and fats. It is suitable for Class A, B, F fires.  
 Internal thermoplastic lining.*

**SPECIFICATIONS**


fire rating	5A 34B 25F
temperature range	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	2l water + AFFF (8%)
propellant agent	20g nitrogen
minimum pressure (+5°C)	16 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



*Thermoplastic cover.*



*Shower effect nozzle*



ELITEX, as manufacturer of fire extinguishers guarantees all its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.



**Fire rating:**  
 Class A, B, F, electrical fires up to 50.000V. Shops, hotels, home.



**Benefits:**  
 Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing. Maximum efficiency, higher than most powder fire extinguishers in the market.



**Do not use for:** class C, D fires.

*Product approved under directive and regulation in force.*



**SERIES: FOAM**  
**MODEL: 6 FOAM ELITE**  
**(special home)**

*Portable fire extinguisher filled with 6 l. of water + AFFF additive.  
 It is suitable for class A, B fires  
 Internal thermoplastic lining.*

**SPECIFICATIONS**

fire rating	27A 233B
temperature range	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	6l water + AFFF (8%)
propellant agent	80g nitrogen
minimum pressure (+5°C)	16 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



*Thermoplastic cover.*



*Shower effect nozzle*



**Fire rating:**  
 Class A, B, electrical fires up to 35.000V. Shops, hotels, home.



**Benefits:**  
 Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing. Maximum efficiency, higher than most powder fire extinguishers in the market.



**Do not use for:** class F, C, D fires.

*Product approved under directive and regulation in force.*

ELITEX, as manufacturer of fire extinguishers guarantees ALL its products in compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.





**SERIES: FOAM**  
**MODEL: 6 FOAM ELITE**  
**(special home)**

*Portable fire extinguisher filled with 6 l. of water + AFFF additive.  
 It is suitable for class A, B fires  
 Internal thermoplastic lining.*

**SPECIFICATIONS**

fire rating	34A 233B
temperature range	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	6l water + AFFF (8%)
propellant agent	80g nitrogen
minimum pressure (+5°C)	16 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



*Thermoplastic cover.*



*Shower effect nozzle*



**Fire rating:**  
 Class A, B, electrical fires up to 35.000V. Shops, hotels, home.



**Benefits:**  
 Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing. Maximum efficiency, higher than most powder fire extinguishers in the market.



**Do not use for:** class F, C, D fires.

*Product approved under directive and regulation in force.*

ELITEX, as a manufacturer of fire extinguishers guarantees ALL its products in compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.





**SERIES: FOAM**  
**MODEL: 6 FOAM "F" ELITE**  
**(special kitchen and home)**

*Portable fire extinguisher filled with 6 l. of water + AFFF additive  
 It is intended for fires caused by use of oils and fats.  
 It is suitable for class A, B, F fires.  
 Internal thermoplastic lining*

**SPECIFICATIONS**

fire rating	27A 233B 75F
temperature range	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	6l water + AFFF (8%)
propellant agent	80g nitrogen
minimum pressure (+5°C)	16 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



*Thermoplastic cover.*



*Shower effect nozzle*



**Fire rating:**

Class A, B, F and electrical fires of up to 35.000V (minimum distance of 1 meter). Restaurants, hotels, home and any kind of kitchen.



**Benefits:**

Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing. Maximum efficiency, higher than most powder fire extinguishers in the market.



**Do not use for:** class C, D fires.

*Product approved under directive and regulation in force.*

ELITEX, as a manufacturer of fire extinguishers guarantees ALL its products in compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.





**SERIES: FOAM**  
**MODEL: 6 FOAM "F" ELITE**  
**(special kitchen and home)**

*Portable fire extinguisher filled with 6 l. of water + AFFF additive  
 It is intended for fires caused by use of oils and fats.  
 It is suitable for class A, B, F fires.  
 Internal thermoplastic lining*

**SPECIFICATIONS**

fire rating	34A 233B 75F
temperature range	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	6l water + AFFF (8%)
propellant agent	80g nitrogen
minimum pressure (+5°C)	16 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



*Thermoplastic cover.*



*Shower effect nozzle*



**Fire rating:**

Class A, B, F and electrical fires of up to 35.000V (minimum distance of 1 meter). Restaurants, hotels, home and any kind of kitchen.



**Benefits:**

Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing. Maximum efficiency, higher than most powder fire extinguishers in the market.



**Do not use for:** class C, D fires.

*Product approved under directive and regulation in force.*

ELITEX, as a manufacturer of fire extinguishers guarantees ALL its products in compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.





ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with CE 2372 on guarantees in the Sale of Consumer Goods.



**SERIES: FOAM**  
**MODEL: 9 FOAM ELITE**  
**(special home)**

*Portable fire extinguisher filled with 9 l. of water + AFFF additive.  
 It is suitable for class A, B fires.  
 Internal thermoplastic lining*

**SPECIFICATIONS**

fire rating	-
temperature range	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	9l water + AFFF (8%)
propellant agent	140g nitrogen
minimum pressure (+5°C)	12,5 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



*Thermoplastic cover.*



*Shower effect nozzle*



**Applications:**  
**Fire rating:**  
 Class A, B, electrical fires up to 35.000V. Shops, hotels, home.



**Benefits:**  
 Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing. Maximum efficiency, higher than most powder fire extinguishers in the market.



**Do not use for:** class F, C, D fires.

*Product approved under directive and regulation in force.*

Portable fire extinguisher with trolley filled with 25 l .  
of water + AFFF additive. It is suitable for class A, B. fires  
Internal thermoplastic lining.

#### SPECIFICATIONS

temperature range	+5°C/+60°C
electrical fires	up to 35.000 V
extinguisher agent	25l water + AFFF
propellant agent	225g nitrogen
minimum pressure (+5°C)	16 bar
working pressure (+20°C)	17,5 bar
maximum pressure (+60°C)	20 bar
testing pressure	30 bar



Thermoplastic cover.



**Fire rating:**  
Class A, B and electrical fires of up to 35.000V. Warehouses, parking areas, shopping malls...



**Benefits:**  
Eco, biodegradable and 100% recyclable. It does not cause choking. It does not hinder vision or breathing.



**Do not use for:** class F, C, D fires.



Manufacturers of fire extinguishers guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.

**EXTINTOR DE INCENDIOS**  
25 LITROS AGUA-ADUSTIVO AFFF

**EXTINTOR DE ALTA EFICACIA**

DESORDENE LA MANERA

TIRE DE LA ANILLA Y PRESIONE LA PALANCA

DIRIJA LA BOQUILLA A LA BASE DE LAS LLAMAS Y APRETE EL CATERLO

NO APTO PARA USO CON TENSIONES SUPERIORES A 35.000 V. A UNA DISTANCIA MINIMA DE 1 METRO

CE

Portable fire extinguisher filled with 2 Kg. of CO<sub>2</sub>  
It is suitable for class B fires

#### SPECIFICATIONS

fire rating	34B
temperature range	-20°C/+60°C
extinguisher agent	2 kg de CO <sub>2</sub>
propellant agent	CO <sub>2</sub>
minimum pressure (-20°C)	19 bar
working pressure (+20°C)	58 bar
maximum pressure (+60°C)	174 bar
testing pressure	250 bar
bursting disc	190 bar



High quality nozzle

Steel cylinder and aluminium dip tube in order to avoid supply disruptions



**Fire rating:**

Class B fires. CO<sub>2</sub>, which by nature is dielectric gas, is suitable for electrical fires. Offices, electrical and electronic material, electrical panels, ...



**Benefits:**

They are clean and gas penetrates and spreads out quickly. It does not conduct electricity. Aluminium probe tube.



**Do not use for:** class A, C, D, F fires.

Product approved under directive and regulation in force.

Portable fire extinguisher filled with 5 Kg. of CO<sub>2</sub>  
It is suitable for class B fires

#### SPECIFICATIONS

fire rating	89B
temperature range	-20°C/+60°C
extinguisher agent	5 kg de CO <sub>2</sub>
propellant agent	CO <sub>2</sub>
minimum pressure (-20°C)	19 bar
working pressure (+20°C)	58 bar
maximum pressure (+60°C)	174 bar
testing pressure	250 bar
bursting disc	190 bar



High quality nozzle



Steel cylinder and aluminium dip tube in order to avoid supply disruptions



**Fire rating:**

Class B fires. CO<sub>2</sub>, which by nature is dielectric gas, is suitable for electrical fires. Offices, electrical and electronic material, electrical panels, ...



**Benefits:**

They are clean and gas penetrates and spreads out quickly. It does not conduct electricity. Aluminium probe tube.



**Do not use for:** class A, C, D, F fires.

Product approved under directive and regulation in force.

ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.

*Portable fire extinguisher filled with 10 Kg. of CO<sub>2</sub>  
It is suitable for class B fires*

#### SPECIFICATIONS

fire rating	-
temperature range	-20°C/+60°C
extinguisher agent	10 kg de CO <sub>2</sub>
propellant agent	CO <sub>2</sub>
minimum pressure (-20°C)	19 bar
working pressure (+20°C)	58 bar
maximum pressure (+60°C)	174 bar
testing pressure	250 bar
bursting disc	195 bar



*High quality nozzle*



*Steel cylinder and aluminium dip tube in order to avoid supply disruptions*



**Fire rating:**

Class B fires. CO<sub>2</sub>, which by nature is dielectric gas, is suitable for electrical fires. Offices, electrical and electronic material, electrical panels, ...



**Benefits:**

They are clean and gas penetrates and spreads out quickly. It does not conduct electricity. Aluminium probe tube.



**Do not use for:** class A, C, D, F fires.

*Product approved under directive and regulation in force.*

ELITEX, as manufacturer of fire extinguishers, guarantees ALL its products of compliance with Law 23/2003 on Guarantees in the Sale of Consumer Goods.



**elitex**<sup>®</sup>  
*providing your safety*

**Elitex Protection, S.L.**  
**Carretera Nacional 320 km. 133,5**  
**16003 Cuenca · ESPAÑA**  
**Tel. +34 969 210 136 · info@elitex.es**  
**www.elitex.es**